# SPECIFICATIONS













THE AUSTIN MOTOR CO., LTD. and AUSTIN MOTOR EXPORT CORPORATION

LTD., Longbridge, Birmingham, England

Printed in England by
J. Howitt & Son Ltd., Nottingham

#### A105 Saloon

Engine—six sylinders 2639 cc.; O.H.V.; (win S.U. carburtters; 102 bb.), @ 4600 r.pm. Single Dry plate clutch 9 in. (0.23 m.) diam. Petrol tank capacity 16 gallom (727 litres). Four-speed synchromeoly gearbos with from the control of the control o

#### **A95 Westminster**

Engine—six cylinders 2639 Cc; O.H.V; single carbureter; 92.h.D., ed. 4500 r.p.m. Single dry plate clutch 9 in (6.23 m) diam. Pertol tank capacity 16 gallons (727 litres). Four-speed synchromesh gearbox (overdrive or auto transmission optional). Hypoid rear ads. Independent from suspendent for the control of the control

#### A95 Countryman

Engine—six cylinders 2699 c.; C.14.N.; single carburetter; 20. h.D., @ 4,500 r.p.m. Single dry plate cultude 9 in. C.2.3 m.) diam. Petrol tank capacity 16 gallons (227 litres). Four-speed synchromesh gearbox (auto-transmission optional), Hypold orar arke. Independent from suspension. 11 in. C.28 m.) diam. byorbutic brakes. or first. Heater and determine the control of the contro

### A55 Cambridge

Engine — Four cylinders, 1489 c.; O.H.V.; single carburetter; 51 hbp., 96
4250 r.p.m. Single dry plate culture is in: 0.20 m of Jun. 0.71 [in: 0.018 m.)
4240 r.p.m. Single dry plate culture is in: 0.20 m of Jun. 0.71 [in: 0.018 m.)
4240 r.p.m. Single dry plate culture is in: 0.20 m of Jun. 0.71 [in: 0.018 m.]
4240 r.p.m. Single dry plate in: 0.40 m. 0.71 [in: 0.018 m.]
4240 r.p.m. Single dry plate in: 0.40 m. 0.40 m.]
4240 r.p.m. Single dry plate in: 0.40 m.]
4240 r.p.m. 0.40 m.]
4240 r.

### A35 Saloon


Engine — Four cylinders 948; C.; O.H.N.; single carburetter; 14 h.b.p., 46,750 r.m. Single dry plate clutte 61; in C-16 m.) dam. Petrol tank capacity 51 gallons (26·13 m.). Four-speed synchromesh gearbox. Hypoid rear axle. Independent front suspension. 7 in. (0·18 m.) diam. hydraulic brakes. 52:0-13 tubeless tyres. Two or four-door, all-steel four seater saloon, standard of de-buse versions. Heater optional. Length 11 ft. 41; in. Width

The information contained in this leaflet is correct at date of publication, but subject to alteration without notice.

DUNDERDALE & YATES LTD.

AUSTIN HOUSE, FISHERGATE
PRESTON: TEL 307617

RESTON TEL 3076/7 PUBLICATION NO. 1466







## A105 de luxe Saloon

With its exciting new styling and superbly upholstered interior, the Austin A108 saloon is fully equipped for the lasting comfort of its occupants. Interior heating and overdrive are fitted as standard items of equipment and the six-cylinder, twin-carburetter, O.H.V. engine produces power in plenty for quick getaway, smooth powerful hill-climbing and fast cruising speeds in safe, super road-holding comfort.

# A55 Cambridge Saloon

Like all other Austins this new A55 saloon is of all-steel unitary construction. With a four-cylinder all-steel unitary construction. With a four-cylinder all this cruising speed with the utmost economy. For increased fuel economy overdrive can be fitted at extra





### O.H.V. Power

All Austin cars have high efficiency overhead valve engines specially developed for use with premium grade fuel. In countries where high grade fuel is not available, low compression engines will be fitted to all models except the AlOS saloon.



### A comfortable interior

The interior of every Austin — big and small — is upholstered in hard wearing materials and designed to give the maximum amount of travel comfort to its occupants.

# Buy AUSTIN — and be proud of it!

